



# CHARGER DC2 60KW CCS 4G PT RAPID

The rapid charger Rapid 60kW is created to deliver power even to the most demanding vehicles. The charging station has been designed to meet the highest requirements and quality standards and offers the best performance in terms of energy management, communication, reliability and efficiency. The chargers are compatible with CCS and have the option of one or two cables in DC charging mode. Load balancing is achieved between the CCS cables or between installed Rapid charging stations in a cluster. In these clusters, DLM 2.0 is included. The charging station is powered by Ingeteam. DC charger 60kW 2pcs CCS, 4,4m usable cable length. 10 inch touchdisplay, MID-meter and prepared for payment terminal.

**E-number**                      **Article number**  
2700892                              354531

## General properties

Type designation	RDC2-CCS-60-4G-PT
Rated current [A]	150
Materials	Stainless steel and aluminium
Colour	Grey
Rated voltage [V AC]	400
AC/DC output	CCS
Cable [m]	5
Standard	EN 61851-1 IEC 61439-7 AEVCS
Netweight [kg]	200
Width [mm]	760
Height [mm]	1950
Depth [mm]	336
Frequency [Hz]	50/60
Temperature range [C]	-35C...+55C
Mounting method	Floor fastening
Degree of protection [IP]	54
Meter	MID-approved
RFID	Yes
Impact strength	IK 10 (Pekskärm IK08)
Communication	4G
Effekt [kW]	60
Stand by [W]	<60

## Specific properties

Name	CHARGER DC2 60KW CCS 4G PT RAPID
E-number	2700892
Article number	354531